



## The Affordable Alternative in New Crushing Equipment

### Specifications

Model	Number of decks	Deck size FEET	Max. feed size INCHES	Bearing size MM	Capacity TPH	Shaft speed RPM	Double amplitude MM	Motor power HP	Weight (Excluding Motor) LBS
RMS410 × 2	2	4 × 10	8	100	50-120	850	8	10	4,381
RMS410 × 3	3	4 × 10	8	100	50-120	850	8	10	5,295
RMS514 × 2	2	5 × 14	16	130	50-200	850	8	20	7,949
RMS516 × 3	3	5 × 16	16	130	100-250	850	8	20	10,659
RMS616 × 3	3	6 × 16	16	140	100-350	850	8	25	11,916
RMS620 × 3	3	6 × 20	16	140	200-450	850	8	30	14,500
RMS820 × 3	3	8 × 20	16	160	300-600	850	8	30	19,300

### Dimensions (Inches)

Model	A	B	C	D	E	F	G	H	J	K	M	N
RMS410 × 2	150 3/8	141 3/4	74	132 7/8	85 1/4	30 3/4	-	37 3/8	48	57 3/8	65 1/4	73 1/8
RMS410 × 3	154 3/8	140 1/2	74	132 1/16	99 1/2	30 3/4	45 1/4	51 1/8	48	57 3/8	65 1/4	73 1/8
RMS514 × 2	199 3/8	189 1/4	110 1/4	170 3/8	110 5/8	37	-	46 1/2	59	69	76 7/8	84 3/4
RMS516 × 3	232 5/8	216 1/8	135 1/2	201 5/8	139 3/8	37	54 3/4	65	59	69	76 7/8	84 3/4
RMS616 × 3	232 5/8	216 1/8	135 1/2	201 5/8	139 3/8	37	54 3/4	65	72	82	89 7/8	97 3/4
RMS620 × 3	280 5/8	264 1/8	180 1/2	246 5/8	155 3/4	37	54 3/4	65	72	79 5/8	89 7/8	100 1/8
RMS820 × 3	292 1/8	272 1/8	180 1/2	251 1/2	175 5/8	39	64 5/8	81 7/8	96	107 7/8	118 1/8	128 3/8

